

PCLC Series Plug-In Power Conditioners

Model Number	Capacity (VA/ W)	Dimensions in inches (H x W x D)	Input Voltage	Output Voltage	Plug Type	Output Receptacles	Shipping Weight (lbs.)
PCLC-110	110/80	5-1/2 x 6-1/2 x 7	120	120	5-15P	(2) 5-15R	12
PCLC-210	210/150	5-1/2 x 6-3/4 x 9-1/2	120	120	5-15P	(4) 5-15R	17
PCLC-420	420/300	5-1/2 x 6-3/4 x 9-1/2	120	120	5-15P	(4) 5-15R	23
PCLC-650	650/450	6-1/2 x 8-1/2 x 11-1/4	120	120	5-15P	(6) 5-15R	28
PCLC-850	850/600	6-1/2 x 8-1/2 x 11-1/4	120	120	5-15P	(6) 5-15R	31
PCLC-1100	1100/800	8-1/4 x 10 x 15	120	120	5-15P	(6) 5-15R	47
PCLC-1400	1400/1000	8-1/4 x 10 x 15	120	120	5-15P	(6) 5-15R	52
PCLC-1800	1800/1200	8-1/4 x 10 x 15	120	120	5-20-P	(6) 5-15R	63

CLC Series Plug-In Power Conditioners

Model Number	Capacity VA/W*	Dimensions (HxWxD) in	Input/output Voltage	Plug Type	Outlets	Approx Weight(lbs)
CLC-0200-AAA	200/140	8 x 6 x 12.5	120/120	5-15P	(2) 5-15R	18
CLC-0350-AAA	350/250	8 x 6 x 12.5	120/120	5-15P	(2) 5-15R	26
CLC-0500-AAA	500/360	10 x 8.75 x 17.25	120/120	5-15P	(4) 5-15R	36
CLC-0750-AAA	750/530	10 x 8.75 x 17.25	120/120	5-15P	(4) 5-15R	42
CLC-1050-AAA	1050/750	10 x 8.75 x 17.25	120/120	5-15P	(4) 5-15R	50
CLC-1500-AAA	1500/1000	10 x 8.75 x 17.25	120/120	5-15P	(4) 5-15R	62
CLC-2100-AAA	2100/1500	11.4 x 11.2 x 18.75	120/120	L5-30P	(4) 5-15R (1) L5-15R	88
CLC-3100-AAA	3100/2200	11.4 x 11.2 x 18.75	120/120	L5-30P	(4) 5-15R (1) L5-15R	114

* Based on a load power factor of 0.7 leading